## **TOP-OF-POLE RACKS**



## **DESIGN FEATURES**

- Gimbals are powder-coated steel, strongbacks are galvanized steel on most models
- Module rails are 6061-T6 structural aluminum extrusions
- Racks are module specific, designed to bottom-bolt using factory holes\*
- Seasonally adjustable from 0° to 60° in 5° increments
- Rail brackets are 6061-T6 structural aluminum angle
- Standard models are rated for 90mph wind loads, 130mph versions available\*\*

TPR	MODULE TYPE AND NOMINAL DIMENSIONS			
NUMBER OF	<b>TYPE 14</b>	<b>TYPE 18</b>	<b>TYPE 21</b>	<b>TYPE 24</b>
MODULES	32" x 62"	39" x 66"	39" x 77"	41" x 81"
1	<b>\$250</b> (2")***	<b>\$280</b> (2")	<b>\$300</b> (2")	<b>\$330</b> (2")
	model SR-TPR1-T14-*	model SR-TPR1-T18-*	model SR-TPR1-T21-*	model SR-TPR1-T24-*
	portrait	portrait	portrait	portrait
2	<b>\$520</b> (3")	<b>\$580</b> (3")	<b>\$680</b> (3")	<b>\$740</b> (3")
	model SR-TPR2-T14-*	model SR-TPR2-T18-*	model SR-TPR2-T21-*	model SR-TPR2-T24-*
	1 row of 2 in portrait	1 row of 2 in portrait	1 row of 2 in portrait	1 row of 2 in portrait
3	<b>\$760</b> (4")	<b>\$880</b> (4")	<b>\$1000</b> (4")	<b>\$1100</b> (4")
	model SR-TPR3-T14-*	model SR-TPR3-T18-*	model SR-TPR3-T21-*	model SR-TPR3-T24-*
	1 row of 3 in portrait	1 row of 3 in portrait	1 row of 3 in portrait	1 row of 3 in portrait
4	<b>\$920</b> (4")	<b>\$1050</b> (4")	<b>\$1210</b> (6")	<b>\$1330</b> (6")
	model SR-TPR4-14-*	model SR-TPR4-T18-*	model SR-TPR4-T21-*	model SR-TPR4-T24-*
	2 rows of 2 in portrait	2 rows of 2 in portrait	2 rows of 2 in portrait	2 rows of 2 in portrait
6	<b>\$1500</b> (6")	<b>\$1800</b> (6")	<b>\$2080</b> (6")	<b>\$2280</b> (6")
	model SR-TPR6-T14-*	model SR-TPR6-T18-*	model SR-TPR6-T21-*	model SR-TPR6-T24-*
	2 rows of 3 in portrait	2 rows of 3 in portrait	2 rows of 3 in portrait	2 rows of 3 in portrait
8	<b>\$1740</b> (6")	<b>\$2380</b> (6")	<b>\$2670</b> (8")	<b>\$2940</b> (8")
	model SR-TPR8-T14-*	model SR-TPR8-T18-*	model SR-TPR8-T21-*	model SR-TPR8-T24-*
	2 rows of 4 in portrait	2 rows of 4 in portrait	2 rows of 4 in portrait	2 rows of 4 in portrait
9	<b>\$2260</b> (6")	<b>\$2630</b> (8")	<b>\$2870</b> (8")	<b>\$3160</b> (8")
	model SR-TPR9-T14-*	model SR-TPR9-T18-*	model SR-TPR9-T21-*	model SR-TPR9-T24-*
	3 rows of 3 in portrait	3 rows of 3 in portrait	3 rows of 3 in portrait	3 rows of 3 in portrait
10	<b>\$2680</b> (8")	<b>\$3380</b> (8")	<b>\$3800</b> (8")	<b>\$4180</b> (8")
	model SR-TPR10-T14-*	model SR-TPR10-T18-*	model SR-TPR10-T21-*	model SR-TPR10-T24-*
	2 rows of 5 in portrait	2 columns of 5 in landscape	2 columns of 5 in landscape	2 columns of 5 in landscape
12	<b>\$3260</b> (8")	<b>\$3710</b> (8")	<b>\$4150</b> (8")	<b>\$4560</b> (8")
	model SR-TPR12-T14-*	model SR-TPR12-T18-*	model SR-TPR12-T21-*	model SR-TPR12-T24-*
	3 rows of 4 in portrait	3 rows of 4 in portrait	3 rows of 4 in portrait	3 rows of 4 in portrait
14	<b>\$3980</b> (8")	<b>\$4520</b> (8")	<b>\$5060</b> (8")	<b>\$5320</b> (8")
	model SR-TPR14-T14-*	model SR-TPR18-T14-*	model SR-TPR21-T14-*	model SR-TPR24-T14-*
	2 columns of 7 in landscape	2 columns of 7 in landscape	2 columns of 7 in landscape	2 columns of 7 in landscape
15	<b>\$4850</b> (8") model SR-TPR15-T14-* 3 columns of 5 in landscape	<b>\$5510</b> (8") model SR-TPR15-T18-* 3 columns of 5 in landscape	NA	NA

\* Please specify the actual module to be mounted.

\*\*Add 25% for the 130mph upgrade (the module layout may vary on some high-wind versions).

\*\*\*The number in () after the price is the size of the mounting pole the rack is made to fit over. Mounting poles are steel pipe, either Schedule 40 or 80. Steel pipe is specified by the nominal ID of the pipe. The mounting pole is supplied by the installer.

We specialize in custom fabrication. Please contact us with your special requirements.

SOLAR RACKWORKS 2615 Princeton Dr NE • Albuquerque, NM 87107 • 505-503-6459 Jeff Randall 505-288-5552 • jeff@solarrackworks.com HIGH-QUALITY MANUFACTURING WITH REASONABLE LEAD TIMES

